

## KF 200

### UPVC & UPVC/ALUMINIUM WINDOW

- Thermal insulation with standard triple glazing  
SOLAR+ ( $U_g = 0.7 \text{ W/m}^2\text{K}$ )  $U_w = 0.99 \text{ W/m}^2\text{K}$
- Best thermal insulation  **$U_w$  up to  $0.81 \text{ W/m}^2\text{K}$**   
(with corresponding glazing)
- Soundproofing up to 45 dB (with corresponding glazing)
- 71 mm construction depth UPVC/aluminium or 68 mm in UPVC
- Narrow view width up to 97 mm
- Triple gasket system
- Fully concealed hardware upon request
- FIX-O-ROUND technology
- Resistance class WK1 and WK2 tested (upon request)
- 5 chamber system
- Locking parts screwed into steel – from a certain window size on
- Standard security
- Shortened aluminium attachment clad available upon request, for thermo-technical optimised construction connection.



**I-tec** Glazing



#### UPVC VERSION

Along with the aluminium attachment clad version in all colours, the classic UPVC version in white is also available.



#### I-TEC GLAZING FIX-O-ROUND TECHNOLOGY

Continuous all around fixing of the glass pane ensures better stability, thermal and sound insulation, burglary protection and functioning security.



#### TRIPLE GASKET SYSTEM

Three continuous gasket levels without interruption ensure high impermeability.